



नरहरिनाथगाउँपालिका गाउँ कार्यपालिकाको कार्यालय

कृष्णलिंगाउँ कालिकोट
कृष्णलिंगाउँ नगरपालिका

क्याटलग सपिड विधिबाट हाईड्रोलिक रक ब्रेकर खरिद सम्बन्धी सूचना

प्रथम पटक प्रकाशित मिति : २०७७/१२/२४

यस कार्यालयमा रहेको एक्साभेटरको लागि एउटा हाईड्रोलिक रक ब्रेकर आवश्यक भएकाले सार्वजनिक खरिद ऐन २०६३ को दफा (८) को उपदफा १ (क) र सार्वजनिक खरिद नियमावली २०६४ को नियम ३१ (ख) बमोजिम हाईड्रोलिक रक ब्रेकर उत्पादन वा वितरण गर्ने उत्पादक वा त्यसको आधिकारीक विक्रेताहरु विच मात्र प्रतिस्पर्धा गराउने क्याटलग(Catalog Shopping)विधिबाट खरिद गर्नुपर्ने भएकाले, ईच्छुक उल्लेखित हाईड्रोलिक रक ब्रेकर विक्री गर्न चाहने उत्पादक वा वितरण गर्ने उत्पादक वा त्यसको आधिकारीक विक्रेताले आ-आफ्नो उत्पादनको आधिकारी स्पेशिफिकेशन, गुणस्तर, मुल्य र सुविधा सहितको विवरण(Catalog/Browser)संगलग्न राखी यो सूचना प्रकाशित भएको मितिले ७ दिन भित्र यस कार्यालयमा सिलबन्दी निवेदन दर्ता गराउन र अन्य आवश्यक कागजात सहित सुचीकृत हुन समेत यो सूचना प्रकाशन गरिएको छ । हाईड्रोलिक रक ब्रेकरको विस्तृत विवरणको लागि यस कार्यालयको वेब साईट www.narharinathmun.gov.np मा हेर्नुहुन समेत अनुरोध छ ।

(Signature)
२०७७/१२/२४

(कविराज न्यौपाने)

नि.प्रमुख प्रशासकीय अधिकृत
प्रमुख प्रशासकीय अधिकृत

www.narharinathmun.gov.np Email. naraharinathgapa@gmail.com

Audio Notice Board No: 1618070768706

TECHNICAL SPECIFICATION OF HYDRAULIC ROCK BREAKER

S.n.	Criteria	Required Specification	Offered Specification
1	General	Hydraulic rock breaker with High power to weight ratio, Easy maintenance and quick repairs, Low maintenance cost, Low noise & vibration, built in valve adjuster to increase power. Must be compatible with EX200Lc model TATA HITACHI make chain excavator and Gross Operating Weight shall not be less than 1700 kg.	Make: Model: Mfg. Year: GW: Country of Origin:
2	Material	Main body material should be at least hardened MS and Chisel and piston material must be 42 chrome steel.	Chisel material: Main body material: Piston material:
3	Operating Pressure	140-185 kg/cm ²	
4	Impact Rate	320-600 Bpm	
5	Operating Weight (including rod)	>1700 kg	
6	Optimum Oil Flow	110-180 L/min	
7	Rod Diameter	135-140 mm	
8	Weight of Base Machine	19-26 Ton	
9	Impact Energy Class	>4400 Joule	
10	Hydraulic & N ₂ Gas	Must be compatible with 68 grade hydraulic oil and normal N ₂ gas	
11	Essential accessories	1. Chisel 2. Seal Kit 3. Grease 4. Breaker Hose Pipe 5. Bracket with Bracket Pin Equipped with all accessories in standard model but not limited to the above items.	Chisel: Seal Kit: Grease in kg: Breaker Hose Pipe: Bracket Pin:
12	Instructions	All signs and instructions in the vibrator shall be in English or Nepali	
13	Manuals	One Copy of the Operator's and Owner's instructions and maintenance manual in English shall be supplied with the vibrator.	



Kamal Bahadur Shahi
Mechanical Engineer

14 Tools

A set of tools as required for general maintenance shall be supplied.

15 Color

Standard color

16 Warranty

Manufacturer shall provide a minimum of six-month warranty after acceptance.

17 Delivery

Hydraulic Rock Breaker shall be delivered to: Naraharinath Rural Municipality, Karnali Province.

PREPARED BY:


Name: Kamal Bahadur Shahi

Designation: Mechanical Engineer

Office: Ministry of physical infrastructure development, Karnali Province

Date: 2077/12/20

Signature:


Kamal Bahadur Shahi
Mechanical Engineer

